

ECA Control

Factsheet



	ECA Stream	ECA Lighting
Suitable for	EVAstream Next 175	Not available
EVAstream functions	Start / stop Speed / timer	Not available
EVAsubaqua functions	Not available	Control up to four lighting groups
Connection EVA Web app	Included as standard	Included as standard
Connection EVA Remote basic	Optional at time of purchase, cannot be upgraded	Not available
Connection EVA System remote	Not available	Not available
Connection EVA Piezo	Not available	Not available

ECA Unit

Dimensions	158 x 119 x 75 mm (LxWxH)	158 x 119 x 75 mm (LxWxH)
IP rating	IP20	IP20
Working temperature	0°C to 35°C, installed in a dry, condensation-free room	0°C to 35°C, installed in a dry, condensation-free room
Warranty	2 years factory warranty	2 years factory warranty

Electrical specifications (input)

Connection voltage (Vac)	230 Vac 10W	230 Vac 10W
Pulse input	Not available	3x potential free (500 ms) - NO

Electrical specifications (output)

PPM output	PPM 1	Not available
Lighting control out	Not available	EVA DMX - DMX 512
Fan output 5W	Not available	24 Vdc 5W

ECA Control

Factsheet



	ECA 1 Essential	ECA 2 Trainer
Suitable for EVAstream type	EVAstream Next 225 - 275 - 350 - 450 - 550	EVAstream Next 225 - 275 - 350 - 450 - 550
EVAstream functions	Start / stop Speed / timer	Start / stop Speed / timer 4 pre-set swim workouts Additional option to create 4 custom swim workouts
EVAsubaqua functions	Optional Control up to four lighting groups Important! The ECA 1 Essential does not include any training programmes and therefore does not have lighting that corresponds to the training programmes	Optional Control up to four lighting groups Compatible with swim workouts Automatic synchronisation with the EVAstream training programs
Connection EVA Web app	Included as standard	Included as standard
Connection EVA Remote basic	Optional	Optional
Connection EVA System remote	Optional	Optional
Connection EVA Piezo	Optional	Optional
ECA Unit		
Dimensions	158 x 119 x 75 mm (LxWxH)	158 x 119 x 75 mm (LxWxH)
IP rating	IP20	IP20
Working temperature	0°C to 35°C, installed in a dry, condensation-free room	0°C to 35°C, installed in a dry, condensation-free room
Warranty	2 years factory warranty	2 years factory warranty
Electrical specifications (input)		
Connection voltage (Vac)	230 Vac 10W	230 Vac 10W
Pulse input	3x potential free (500 ms) - NO	3x potential free (500 ms) - NO
Electrical specifications (output)		
PPM output	PPM 2	PPM 2
Lighting control out	EVA DMX - DMX 512	EVA DMX - DMX 512
Fan output 5W	24 Vdc 5W	24 Vdc 5W

ECA Control

Factsheet



ECA 3 ProTrainer

Suitable for EVAstream type	EVAstream Next 225 - 275 - 350 - 450 - 550
EVAstream functions	Start / stop Speed / timer 3 complete training programs with 20 pre-set swim workouts Additional option to create 4 custom training programmes with multiple swim workouts
EVAsubaqua functions	Optional Control up to four lighting groups Compatible with swim workouts Automatic synchronisation with the EVAstream training programs
Connection EVA Web app	Included as standard
Connection EVA Remote basic	Optional
Connection EVA System remote	Optional
Connection EVA Piezo	Optional

ECA Unit

Dimensions	158 x 119 x 75 mm (LxWxH)
IP rating	IP20
Working temperature	0°C to 35°C, installed in a dry, condensation-free room
Warranty	2 years factory warranty

Electrical specifications input

Connection voltage (Vac)	230 Vac 10W
Pulse input	3x potential free (500 ms) - NO

Electrical specifications output

PPM output	PPM 2
Lighting control out	EVA DMX - DMX 512
Fan output 5W	24 Vdc 5W